







Light Curtain Sensors

List of models

(*) Certain detecting conditions apply. See data for details.

Series name Overview	Appearance/shape	Model	Detecting width	Light axis interval	Detecting distance	Detecting object (*)	See page
SSR Reflector type	Reflector type 	SSR304	140mm	40mm	0.4-3m	φ 60mm min.	314
		SSR306	220mm				
		SSR308	300mm				
		SSR310	380mm				
		SSR312	460mm				
SST100 Generic type	Through-beam type 	SST104	120mm	40mm	10m max. (15m max. for H type)	φ 60mm min.	318
		SST108	280mm				
		SST112	440mm				
		SST116	600mm				
		SST120	760mm				
		SST124	920mm				
MST Separate output for each light axis	Through-beam type 	MST104	120mm	40mm	10m max.	φ 60mm min.	320
		MST108	280mm				
		MST112	440mm				
		MST116	600mm				
		MST120	760mm				
		MST124	920mm				
SST300 For pipe and bar steel detection	Through-beam type 	SST316	150mm	10mm	2m max.	φ 15mm min.	322
		SST332	310mm				
		SST348	470mm				
		SST364	630mm				
		SST396	950mm				
SS-CH Output according to combination of light axes		See the pages shown on the right for details.					324

 **Caution** The Light Curtain Sensor Series is not intended for press machine safety use. Do not use for press machine safety purposes.